

Standard-Peltierelemente

Betriebstemperatur max. 80°C

Länge der Anschlusskabel > 100 mm

Empfohlener Anpressdruck: 35-50 N/cm²

Typ	bei Warmseitentemp. 25°C				Ri	Thermo	Wärme-	Abmessung
	I _{max}	U _{max}	Q _{kmax} @ΔT=0	ΔT _{max} @Q _k =0				
	[A]	[V]	[W]	[K]	[Ohm]	[mV/K]	[mW/K]	[mm]
PKE ...								
127 A 2418	14	14.3	116	59	0.85	49	1250	62 x 62 x 5,2
127 A 2013	14	14.3	110	58	0.89	48	1180	50 x 50 x 3,6
127 A 2427	9	14.3	79	60	1.25	50	860	62 x 62 x 5,8
127 A 0023	8	14.3	72	62	1.6	48	670	40 x 40 x 3,4
127 A 0021	6	14.3	51	62	2.5	50	435	40 x 40 x 3,8
127 A 0020	4	14.3	33	62	3.5	51	320	40 x 40 x 4,7
127 A 1027	3.9	14.3	32	62	3.2	48	320	30 x 30 x 3,4
127 A 1020	2.5	14.3	21	62	5.4	50	200	30 x 30 x 4,0
71 A 0021	6	8	28	62	1.4	28	243	30 x 30 x 4,0
71 A 0020	4	8	18	62	2	28.5	179	30 x 30 x 4,7
35 A 0020	4	4	9	62	1	14	88	30 x 15 x 4,7
31 A 0020	4	3.8	8	62	0.85	12.4	78	20 x 20 x 4,7
17 A 0021	6	2	6.8	62	0.33	6.7	58	15 x 15 x 4,0
17 A 0020	4	2	4.4	62	0.5	6.8	43	15 x 15 x 4,7
7 A 0021	6	0.8	2.8	62	0.14	2.7	24	10 x 10 x 4,0